


Water

Discharge

 Refer to warnings and safety information on pages M-1 – M-15.

Use of damaged hose or improper use may result in bodily injury or property damage. Please consult Eaton catalog or Technical Support for proper application.

EHW029

OTTER™ Layflat Water Discharge



Construction:

Tube: EPDM

Reinforcement: High-tensile synthetic textile

Cover: EPDM

Operating Temperature:

-40°C to +120°C
(-40°F to +248°F)

Application:

- For water discharge

Markets:

- Agriculture
- Construction
- Equipment rental
- Mining
- Ship building
- Oil and gas exploration
- Tank truck

Type of Couplings:

- Shank type male x female
- Cam and groove

Contact coupling manufacturer for attachment procedure and other coupling recommendations

# Part No.	Hose I.D.			Hose O.D.		Max Oper Pressure		Burst Pressure		Weight		Length	
	DN	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHW029-20-100	31	31,8	1.25	38,0	1.50	10,5	150	31,5	450	0,45	0.30	30,5	100
EHW029-24-100	38	38,1	1.50	44,0	1.73	10,5	150	31,5	450	0,52	0.35	30,5	100
EHW029-32-100	51	50,8	2.00	57,0	2.24	10,5	150	31,5	450	0,73	0.49	30,5	100
EHW029-40-100	60	63,5	2.50	70,0	2.76	10,5	150	31,5	450	0,90	0.60	30,5	100
EHW029-48-100	80	76,2	3.00	83,0	3.27	10,5	150	31,5	450	1,15	0.77	30,5	100
EHW029-64-100	102	101,6	4.00	109,0	4.29	10,5	150	31,5	450	1,67	1.12	30,5	100
EHW029-80-100	130	127,0	5.00	136,0	5.35	10,5	150	31,5	450	2,51	1.69	30,5	100
EHW029-96-100	150	152,4	6.00	162,0	6.38	10,5	150	31,5	450	3,36	2.26	30,5	100
EHW029-128-100	200	203,2	8.00	216,5	8.52	10,5	150	31,5	450	5,94	3.99	30,5	100
EHW029-160-100	250	254,0	10.00	268,0	10.55	10,5	150	31,5	450	8.00	5.37	30,5	100
EHW029-192-100	305	304,8	12.00	320,0	12,60	10,5	150	31,5	450	8,70	5.84	30,5	100