

H0307 and H0379 LEADER™ Water Discharge



Construction:

Tube: EPDM

Reinforcement: 2-ply,
2 or 4-spiral fiber

Cover: EPDM

Operating Temperature:

-23°C to +66°C
(-10°F to +150°F)

Application:

- For water discharge

Markets:

- Mining
- Construction
- Equipment rental
- Ship building
- Tank truck

Type of Couplings:

- Cam and groove
- Combination nipple

Contact coupling manufacturer for attachment procedure and other coupling recommendations

# Part No.	Hose I.D.		Hose O.D.		Max Oper Pressure		Burst Pressure		Weight		Length		
	DN	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
H0307													
H030724-100	38	38,1	1.50	45,7	1.80	7,0	100	20,7	300	0,85	0.57	30,5	100
H030732-100	51	50,8	2.00	58,7	2.31	7,0	100	20,7	300	1,09	0.73	30,5	100
H030740-100	60	63,5	2.50	73,5	2.89	7,0	100	20,7	300	1,34	0.90	30,5	100
H030748-100	80	76,2	3.00	86,5	3.41	7,0	100	20,7	300	1,64	1.10	30,5	100
H030764-100	102	101,6	4.00	111,9	4.41	7,0	100	20,7	300	2,16	1.45	30,5	100
H030796	150	152,4	6.00	161,8	6.37	5,5	80	17,2	250	3,18	2.14	15,2	50

H0379

H037924-100	38	38,1	1.50	52,4	2.06	10,5	150	31	450	0,95	0.64	30,5	100
H037932-100	51	50,8	2.00	65,1	2.56	10,5	150	31	450	1,26	0.85	30,5	100
H037940-100	60	63,5	2.50	73,9	2.91	10,5	150	31	450	1,55	1.04	30,5	100
H037948-100	80	76,2	3.00	90,5	3.56	10,5	150	31	450	1,83	1.23	30,5	100
H037964-100	102	101,6	4.00	115,9	4.56	10,5	150	31	450	2,40	1.61	30,5	100
H037980-100	130	127,0	5.00	137,5	5.41	10,5	105	31	450	3,08	2.07	30,5	100
H037996	150	152,4	6.00	163,9	6.45	10,5	150	31	450	3,79	2.55	15,2	50
H037996-100	150	152,4	6.00	163,9	6.45	10,5	150	31	450	3,79	2.55	30,5	100