


# MatchMate™

## TTC Series Fittings

### Split Flange 45° Tube Elbow (SAE Code 61)



TTC Part #	Flange Head Dia. K Ø	Hose Size	A		Hose Cut-Off Factor (D)		EØ		H	
			mm	in	mm	in	mm	in	mm	in
1A8FLA8	1.19	-08	79,0	3.11	49,3	1.94	9,4	0.37	19,8	0.78
1A12FLA8	1.50	-08	92,5	3.64	62,7	2.47	9,4	0.37	25,4	1.00
1A12FLA10	1.50	-10	93,5	3.68	64,3	2.53	11,7	0.46	25,4	1.00
1A12FLA12	1.50	-12	93,2	3.67	63,0	2.48	14,7	0.58	25,7	1.01
1A16FLA12	1.75	-12	105,7	4.16	75,4	2.97	14,7	0.58	26,9	1.06
1A16FLA16	1.75	-16	110,5	4.35	76,2	3.00	19,3	0.76	26,9	1.06
1A20FLA16	2.00	-16	122,2	4.81	87,6	3.45	19,3	0.76	29,2	1.15
1AT16FLA20**	1.75	-20	121,9	4.80	77,7	3.06	19,3	0.76	26,9	1.06
1AP16FLA20*	1.75	-20	121,9	4.80	77,7	3.06	19,3	0.76	26,9	1.06
1AT20FLA20**	2.00	-20	134,1	5.28	90,2	3.55	25,7	1.01	30,0	1.18
1AP20FLA20*	2.00	-20	134,1	5.28	90,2	3.55	25,7	1.01	30,0	1.18
1AT24FLA20**	2.37	-20	150,9	5.94	106,7	4.20	25,7	1.01	35,8	1.41
1A24FLA24	2.37	-20	150,9	5.94	106,7	4.20	25,7	1.01	35,8	1.41
1A32FLA24	2.81	-24	154,2	6.07	108,0	4.25	32,0	1.26	35,8	1.41
1A24FLA24	2.37	-32	159,3	6.27	109,0	4.29	32,0	1.26	35,8	1.41
1A32FLA32	2.81	-32	190,2	7.49	140,2	5.52	44,5	1.75	50,8	2.00

\* Uses 1-wire braid socket

\*\* Uses 2-wire braid socket