


# MatchMate™

## TTC Series Fittings

### Split Flange Straight (SAE Code 61)



TTC Part #	Thd. Flange Head Dia. K Ø	Hose Size	A		Hose Cut-Off Factor (D)		EØ	
			mm	in	mm	in	mm	in
1A8FL8	1.19	-08	82,0	3.23	52,3	2.06	9,7	0.38
1A12FL8	1.50	-08	83,1	3.27	53,3	2.10	9,7	0.38
1A12FL10	1.50	-10	82,8	3.26	53,3	2.10	12,7	0.50
1A12FL12	1.50	-12	84,1	3.31	53,8	2.12	15,5	0.61
1A16FL12	1.75	-12	84,1	3.31	53,8	2.12	15,5	0.61
1A20FL12	2.00	-12	91,7	3.61	61,5	2.42	15,5	0.61
1A16FL16	1.75	-16	88,6	3.49	54,4	2.14	20,8	0.82
1A20FL16	2.00	-16	96,3	3.79	62,0	2.44	20,8	0.82
1AT16FL20**	1.75	-20	100,1	3.94	56,1	2.21	20,8	0.82
1AP16FL20*	1.75	-20	100,1	3.94	56,1	2.21	20,8	0.82
1AT20FL20**	2.00	-20	107,7	4.24	63,8	2.51	26,7	1.05
1AP20FL20*	2.00	-20	107,7	4.24	63,8	2.51	26,7	1.05
1AT24FL20**	2.38	-20	108,5	4.27	64,5	2.54	26,7	1.05
1AP24FL20*	2.38	-20	108,5	4.27	64,5	2.54	26,7	1.05
1AT32FL20**	2.81	-20	108,5	4.27	64,5	2.54	25,7	1.01
1A24FL24	2.38	-24	111,8	4.40	65,5	2.58	32,0	1.26
1A32FL24	2.81	-24	111,8	4.40	65,5	2.58	30,2	1.19
1A32FL32	2.81	-32	117,1	4.61	66,8	2.63	44,5	1.75
1A40FL32	3.31	-32	116,8	4.60	66,8	2.63	44,5	1.75

\* Uses 1-wire braid socket

\*\* Uses 2-wire braid socket